

Paramètres de coupe indicatifs

Empfohlene Schnittwerte



Standard machining data

Matière Werkstoff Material	Tournage Drehen Turning		Tronçonnage Abstechen Cut off	
	VC (m/min)	F (mm/U)	VC (m/min)	F (mm/U)
Acier de décolletage Automatenstahl Free-cutting steel	120 - 200	0.01 - 0.20	80 - 150	0.01 - 0.15
Acier Stahl < 600 N/mm ² Steel	80 - 160	0.01 - 0.18	70 - 120	0.01 - 0.12
Acier Stahl < 800 N/mm ² Steel	60 - 120	0.01 - 0.15	60 - 100	0.01 - 0.10
Acier Stahl < 800 N/mm ² Steel	50 - 100	0.01 - 0.12	40 - 80	0.01 - 0.08
Acier inoxydable Rostfreistahl Stainless steel	60 - 120	0.01 - 0.15	60 - 100	0.01 - 0.08
Aluminium	180 - 800	0.01 - 0.30	150 - 300	0.01 - 0.20
Titane Titan Titanium	30 - 70	0.01 - 0.12	30 - 50	0.01 - 0.06
Cuivre, laiton, bronze Kupfer, Messing, Bronze Copper, brass, bronze	100 - 500	0.01 - 0.30	100 - 300	0.01 - 0.20

Accessoires

Zubehör

Accessories

Porte-outils Halter Holders			Option
250-... / 260-...	V-M4X9-T15	C-T15	SET-NM-TX15
250-8 / 260-8	V-M3.5X7-T15		
250RC / 260-C	V-M4X7.3-T15		

Recommandation de serrage
Drehmoment Empfehlung
Clamping recommendation

3.0 Nm



SET-NM-TX15